TYPE 2 LATCH AND TYPE 2 RSL SLOTTED RECEIVER

THIS SHALLOW RECEIVER CAN BE MOUNTED FLUSH AND BLIND IN VERY THIN PANELS RECEIVER DEPTH IS ONLY 1/2" (12.7mm)




Fig. 1

Application : Thin panel partitions where in-line butt joints, corner and 'T' joints occur.

USED ON:

- Exhibits
- Counters
- Store Fixtures
- Doors




Fig. 2

Mounting : Here a typical corner or 'T' joint is shown using a Type 2 Latch and RSL Receiver. S1250-2-1.125 & RSL500-2-187.

USED ON:

- Pre-fab structures
- Office panels
- Partitions
- Cases




Fig. 3

4-way post mountings using slim line paneling are feasible using Type 2 Latches and the RSL Receivers.

USED ON:

- Safety shields
- Saunas
- Student carrels
- Enclosures




Fig. 4

PANEL MOUNTING DIMENSIONS
Type 2 Latch & Type 2 RSL Receiver
* S1250-2-1.125 & RSL500-2-187




Fig. 5

TYPE 2 LATCH DIMENSIONS
S1250-2-1.125




Fig. 6

TYPE 2 RSL RECEIVER DIMENSIONS
RSL500-2-187

 © 2009